Orion Energy Systems

Exterior Uplighting Fixture Series

Reduce your energy waste and maintenance costs by implementing energy efficient exterior lights by Orion. The optically and thermally efficient designs utilize proven T5 fluorescent technology to provide a whiter, brighter light with superior lumen maintenance, improving safety and visibility.

APPLICATIONS Ideal for uplighting billboards, signs, and walls.

CONSTRUCTION Single piece body comprised of 18 gauge galvanized steel. Frame fits over fixture body to allow water run-off.


FINISH Standard finishes available in Black, Bronze, Gray, and White. Custom finishes are also available. >90% fixture efficiency.

CERTIFICATION UL Listed for Wet Locations

ELECTRICAL Hardwired power connection, T5 programmed start ballast.

REFLECTOR Options include:

- Miro-4 high bay reflectors with 95% total reflectance and patented, parabolic shape.
- Forward throw reflectors with 95% total reflectance and unique reflector shape that directs light to the front of the fixture.



XUT4-2FT with XUAV-AY Bracket

SPECIFICATIONS

Series	Fixture Length	Lamps	W	attage Consum	ed
XUT / XUS	2 Foot Fixture	2 Lamps	54@120v	53@277v	57@480v
XUT / XUS	2 Foot Fixture	3 Lamps	82@120v	80@277v	86@480v
XUT / XUS	2 Foot Fixture	4 Lamps	108@120v	105@277v	113@480v
XUT	2 Foot Fixture	6 Lamps	164@120v	160@277v	172@480v
XUT / XUS	4 Foot Fixture	4 Lamps	232@120v	226@277v	240@480v
XUT	4 Foot Fixture	6 Lamps	348@120v	340@277v	360@480v

Series	Length	Width	Depth
XUT2-2FT, XUT3-2FT, XUT4-2FT	24.33"	12.88"	2.68"
XUS2-2FT, XUS3-2FT	24.33"	14.38"	3.15"
XUT4, XUS3	47.93"	14.38"	3.15"
XUT6-2FT, XUS4-2FT	24.33"	18.13"	3.15"
XUT6, XUS4	47.93"	18.13"	3.15"

ORDERING INFORMATION

 $XU \times$ Series

XXWeather Options

Number of Lamps

XXFixture

Lenath

XX Voltage

XXConnection Type

Finish

XX Lamp Type

Series		
XUT	Exterior Uplighting Fixture with Miro-4 High Bay Reflectors	
XUS	Exterior Uplighting Fixture with Forward Throw Reflectors	

Weather Options		
(blank)	Standard Fixture	
Z	Cold Weather	

Number of Lamps		
2	2-Lamp T5	
3	3-Lamp T5	
4	4-Lamp T5	
6	6-Lamp T5 (XUT only)	

Fixture L	Fixture Length		
(blank)	ank) 4 Foot Fixture		
2FT	2 Foot Fixture		

Voltage	
(blank)	120v–277v
480	480v, Internal Transformer

Connection Type	
(blank) Full Switch	
DS	Dual Switch

Finish*	+
BL	Black
BR	Bronze
GR	Gray
WH	White
*Consult f	actory for ish information.

Lamp Type*	
3K	3000°K
35K	3500°K
41K	4100°K
5K	5000°K

^{*}The standard lamp in the 2ft fixture is 24 watts (5000°K). The standard lamp in the 4ft fixture is 54 watts (5000°K).



877.204.7540

www.oesx.com

NYSE Amex: OESX

